

# KOMFI® - DELTA 52

## COMMERCIAL LAMINATING SYSTEM


The **Delta 52** laminator is well-known as the legendary machine that revolutionized one-sided laminating. The **Delta 52** consistently delivers. Continually updated and improved, the current Delta easily keeps its place as the benchmark for all production one-sided laminators.



### FEATURES

- Robust and reliable solution for on demand and commercial lamination
- Automatic sheet feeding via Komfi® designed feeding head
- Laminating nip roller heated with 3 zone electrical heating system
- Automatic sheet separation using cutting knives
- Application: medium to high volume printing, publishing and packaging production
- Suitable for round-the-clock industrial production

 115' per minute

 max. 21.3"W x 29.9"L

**Innové**<sup>®</sup>  
GLOBAL SOLUTIONS

The Global Source for Print Finishing Solutions

Visit us online for a complete list of locations around the world.

800.820.0641 | [inquiries@innove.net](mailto:inquiries@innove.net) | [www.innove.net](http://www.innove.net)

# KOMFI® - DELTA 52

## COMMERCIAL LAMINATING SYSTEM

### FEATURES



#### INTEGRATED DEEP PILE FEEDER

Automatic sheet feeding with Komfi® designed high-performance feeding head.



#### CENTRALIZED CONTROL CENTER

Intuitively designed control center is easy to access and use.

### OPTIONS

- Film slitter
- Additional perforator
- Built-in perforator
- Film loading equipment
- Jogging table
- Antistatic bar
- Automatic stacker (onto pallet)
- External embossing equipment
- Preventative maintenance spare parts kit

Description	Specifications
Dimension	105"L x 49"W x 57"H
Max. Laminating Speed	115 ft/min
Maximum Output	3180 sheets/hr (20" x 26")
Minimum Sheet Dimensions	7.9" x 7.9"
Maximum Sheet Dimensions	21.3" x 29.9"
Paper Weight Range	60 lb. text - 18 pt. cover
Thickness of Laminating Film	1.0 - 2.2 mil
Kind of Laminating Film	OPP, PET, Nylon
Warm Up Time	3 minutes
Sheet Overlap Accuracy	± 1/16"