

4.75 mil PSA Adhesive Backed Laminate Film

AVAILABLE IN: 54" x 150'

Stellar Indoor FloorGrip offers a slip resistant, semi-transparent, slightly textured (emboss) surface durable for indoor use. This cold/PSA film can be applied cold / with moderate heat.

SUGGESTED USES

- · For use with floor graphic applications
- UL-410 approved for slip resistance



	Specifications
Film Thickness / Adhesive Thickness	3.75 mil polyolefin / 1 mil clear permanent acrylic adhesive
Durability	Indoor use only
Liner	1.2 mil clear film
Gloss Level	38 (avg.) @ 60°
Minimum Application Temperature	+50° F (minimum for substrate)
Service Temperature Range	-40° F to +180° F (-46° C to + 82° C)
Chemical Resistance	Resistant to ammonium hydroxide - 10%, detergent, distilled water, gasoline and hydrochloric acid - 10%
Typical Adhesion Values	180° Peel Test Substrate Stainless Steel 4.7 lb/in
Shelf Life	1 year from ship date when stored in proper conditions 70° F and 50% relative humidity.
Dimensional Stability	No measurable shrinkage

Note: The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)



Finish Well

GVDirect™ diligently works to ensure our performance lineup of laminate films, digital technologies, equipment, and all things finishing work for our customers to gain consumer attention and market share. GVDirect™ diligently endeavors to deliver value in service, product, and equipment that surpass market demands, support productivity, and uphold social and environmental integrity.