Overlaminate Thermal Roll Film

TALENT (GENIUS) Leather

GeniusLeather[™] overlaminate offers allure and tactile dimension to the print, publishing and packaging world. Manufactured with a unique emboss pattern on the film, GeniusLeather™ simulates the texture of high-quality fine-grained leather. The smooth cowhide pattern gives a subdued, yet expensive feel on every application.

KEY BENEFITS

- Superb Color Tonality and Clarity
- Rich Dimensional Grain Pattern

COMMON APPLICATIONS

Electronics Packaging

Scuff and Scratch Resistant Finish

Cosmetic and Jewelry Packaging

• Media/Binders and Slip Cases

- Accepts Spot UV
- Glueable and Stampable



Properties	Side	Value	Unit	Test Method / Standard
Thickness		1	Mil	Talent™ - Method
		26	Microns	
Transparency		91.8	%	ASTM D 1003
Haze		61	%	ASTM D 1003
Gloss		6-8	%	Talent [™] - Method
Dyne Level		38-40	Dyne	Talent [™] - Method
Coefficient of Friction	В	0.39		DIN EN ISO 8295
Application Temperature	А	220-240°F (105-115°C)	°F (°C)	Various Equipment - Always Test
Laminate Tensile Strength	MD	93.9	N/mm ²	ASTM D 882
	TD	169.1	N/mm ²	

A = Adhesive Side B = BOPP Side MD = Main Direction TD = Transverse Direction

Note: The information given above is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. GVDirect[™] makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The above data is purely for reader's consideration, investigation and verification.



GVDirect™ diligently works to ensure our Talent™ lineup of laminate films, digital technologies, equipment, and all things finishing work for our customers to gain consumer attention and market share. GVDirect™ diligently endeavors to deliver value in service, product, and equipment that surpass market demands, support productivity, and uphold social and environmental integrity.



gvdirect.com





1.877.526.6848