

# KAYM 92 PLS

Paper Cutter

Made in  
Turkey



36.22"

Max. Cutting Width

**GVDIRECT™**

Finish Well

GVDirect™ diligently works to ensure our performance lineup of laminate films, digital technologies, equipment, and all things finishing work for our customers to gain consumer attention and market share. GVDirect™ diligently endeavors to deliver value in service, product, and equipment that surpass market demands, support productivity, and uphold social and environmental integrity.

1.877.526.6848

[gvdirect.com](http://gvdirect.com)

# KAYM 92 PLS

- Digital Coordinate Measurement and Indicators (7" LCD Coloured Touchscreen)
- 1.000 programs x 75 program steps
- 75.000 pcs. program position memory
- Sortings programs in numeric and alphabetic
- Manual/ Semi-Automatic/ Full-Automatic Operation Modes
- Label Programming
- Equal (endless) Division-Program
- Memorization of Cutting-Position Program
- Indicator of Cutting-Quantity
- Backgauge controll in absolute and incremental system by program
- Automatic backgauge orientation by forward-rearward buttons
- Sensitive positioning of backgauge by hand-wheel
- Calculator Function
- Turkish, English and Arabic Language Packages
- Pneumatic (Air Cushion) Table (easy movement capability)
- Chrome Plated Table (stainless surface)
- Table Light
- Cutting Light Line function
- Three-phase (380V / 50Hz) Electrical System
- Lockable Main Switch
- Servo Motor
- Linear Guide
- Precision-Ball Screw
- Hydraulic Clamping, min-max. pressure adjustment
- Gradual Pressure by foot pedal
- Eccentric-Driven Cutting System
- Double-Hand Button Security System
- Knife Holder Safety Mechanism (Mechanical Lock)
- Light Barrier Security Protection (Photocells)
- Built-in Knife Lifting Device for quick change
- The Backgauge Angulation and Skewness Removal System

Specifications	
<b>Cutting Width</b>	36.22" (920 mm)
<b>Feeding Depth</b>	0.03" (1.000 mm)
<b>Feeding Height Max. (without false plate)</b>	4.72" (120 mm)
<b>Front Table Length (D)</b>	29.92" (760 mm)
<b>Table Height</b>	35.43" (900 mm)
<b>Min. Max Clamp Pressure</b>	150/3.500 daN
<b>Knife Speed ( by direct command)</b>	45 cycles / min.
<b>Knife Grinding Reserve Max.</b>	1.37" (35 mm)
<b>Smallest Cut Without False Plate, Manual</b>	0.98" (25 mm)
<b>Smallest Cut With False Plate, Automatically</b>	3.34" (85 mm)
<b>Power Supply</b>	4 Kw
<b>Backgauge Power Supply</b>	0.75 Kw
<b>BKnife Dimensions (L x W x Thickness)</b>	0.04" x 4.5" x 0.46" (1.095 mm x 115 mm x 11.7 mm)
<b>Width with Side Tables (B)</b>	0.082" (2.090 mm)
<b>Depth (A)</b>	0.088" (2.251 mm)
<b>Depth Frame (C)</b>	32.67" (830 mm)
<b>Height Frame (E)</b>	0.059" (1.516 mm)
<b>Total Weight (brut)</b>	4.4 lb (2.000 kg)
<b>Pneumatic (Air Cushion) Side Tables (Right &amp; Left)</b>	Optional

Note: The information given above is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. GVDirect™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The above data is purely for reader's consideration, investigation and verification.