


KOMFI® AMIGA 76

Available in
Canada




Thermal Laminator



Max. Speed
25m per minute



3.5 minute
Warm Up



208V / 30 amp
3 Phase
Nema L14-30



GVDIRECT™

Finish Well

GVDirect™ diligently works to ensure our performance lineup of laminate films, digital technologies, equipment, and all things finishing work for our customers to gain consumer attention and market share. GVDirect™ diligently endeavors to deliver value in service, product, and equipment that surpass market demands, support productivity, and uphold social and environmental integrity.

1.877.526.6848

gvdirect.com

KOMFI® AMIGA 76

Made in
Czech Republic



The Amiga 76 offers professional quality lamination for a variety of applications up to 29.75" x 44". Modular design can provide a professional laminating solution for any situation. The Amiga 76 features an electronically controlled feed gate for accurate and stable sheet overlap at any production speed. Graphical touch screen offers easy, multi-language operation and fast setup due to user presets to recall machine settings quickly. Continuous monitoring of the whole lamination process (feeding, temperature, air pressure, sheet separation, etc.) to ensure 100% quality control.

FEATURES

- Low investment to gain professional quality lamination capabilities.
- Unique software features to minimize wastage.
- Double operator panel for accessing key controls.
- Laminating rollers easily accessible via side opening for easy maintenance.
- Designed for unattended operation.
- Built-in help and self-diagnostics.
- Processor controlled feeding head provides accurate sheet feeding.
- Additional processor controlled separation air blowers for reliable sheet feeding.
- Electronically controlled gate for accurate and consistent sheet overlap at any production speed.
- Graphical touch screen for simple multi-language operation.
- Continuous automatic checking of the whole lamination process (feeding, temperature, air pressure, sheet separation, etc.) to ensure 100% quality control.

Top Feed Specifications	
Dimensions	145.6" L x 50" W x 62.9" H (Including Delivery Desk)
Speed	25 m/min
Warm-Up Time	3.5 minutes
Paper Weight	115 - 600 g/m ²
Sheet Size	Min. 12" W x 9" L / Max. 29.75" W x 44" L
Film Thickness	1.0 - 3.0 mil (3" Core)
Laminate Film	OPP, PET, Nylon
Sheet Overlap Accuracy	± 3/64" (at constant)
Power Requirements	3 Phase / 208 Volt / 30 amp. Laminator comes with Hubbell Brand Connector #HBL2713 and Hubbell Brand Flanged Receptacle #HBL2716

Note: The information given above is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. GVDirect™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The above data is purely for reader's consideration, investigation and verification.

GVDirect™ offers a complete lineup of laminate films and all things finishing that work flawlessly with our equipment. Visit us online or contact us directly for details and pricing.

