

GUOWEI F SERIES

92F / 115F / 130F PROGRAM CONTROL PAPER CUTTER



36"

Max. Cutting Width

92F

45"

Max. Cutting Width

115F

51"

Max. Cutting Width

130F

GVDIRECT™

Finish Well

GVDirect™ diligently works to ensure our performance lineup of laminate films, digital technologies, equipment, and all things finishing work for our customers to gain consumer attention and market share. GVDirect™ diligently endeavors to deliver value in service, product, and equipment that surpass market demands, support productivity, and uphold social and environmental integrity.

1.877.526.6848

gvdirect.com

GUOWEI F SERIES

92F PROGRAM CONTROL PAPER CUTTER

Japan alternative digital servo control technology; 15-inch colorful touching LCD. The data resolution rate is 0.01mm. It has self-diagnostic function of troubles and displays the operating pattern, and has 300 program units, over 30000 different cutting positions, dynamic display of cutting and running, dynamic tracking, max feeding speed 8-30m/min (166/186/220/260 paper pushing speed 5-20m/min).

Powerful computer operating system with more functions and it can store and memorize things. The storage time can be up to 300,000 hours with self-maintenance of the operating system. Hydraulic components are adopted from Italy, electrical components from France, Germany, Japan, Korea, Taiwan ball lead screw, Linear double guide rails, PLC control system are adopted to monitor all mechanical implementation, its key parts adopt imported bearing of low maintenance.

Technical Parameters:

	Specifications
Model	92F
Cutting width	36" (92 cm)
Max cutting height w/o pressing plate	5.12" (13 cm)
Max. cutting Depth	36" (93 cm)
Max cutting depth w/o assistance pressing plate	0.91" (2.3 cm)
Extended length of working table	25.59" (65 cm)
Height (Working Table)	33.86" - 35.43" (86-90 cm)
Machine Width w/ side working table	91.73" (233 cm)
Total length (Working Table)	77.95" (198 cm)
Cutting speed (r/min)	45

	Specifications
Max. Paper pressure	35000
Power - Main Motor (kw)	3
Motor - Paper Feeding (kw)	0.75
Air Pump (kw)	0.55
Machine Weight (kg)	2800 kg (6172.94 lbs)
Overall Dimension (L x W x H)	89.76" x 55.12" x 76.77"

Optional Large Side Table Set



Note: The information given above is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. GVDirect™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The above data is purely for reader's consideration, investigation and verification.

GVDIRECT™

Finish Well

GVDirect™ diligently works to ensure our performance lineup of laminate films, digital technologies, equipment, and all things finishing work for our customers to gain consumer attention and market share. GVDirect™ diligently endeavors to deliver value in service, product, and equipment that surpass market demands, support productivity, and uphold social and environmental integrity.

1.877.526.6848

gvdirect.com

GUOWEI F SERIES

115F PROGRAM CONTROL PAPER CUTTER

Japan alternative digital servo control technology; 15-inch colorful touching LCD. The data resolution rate is 0.01mm. It has self-diagnostic function of troubles and displays the operating pattern, and has 300 program units, over 30000 different cutting positions, dynamic display of cutting and running, dynamic tracking, max feeding speed 8-30m/min (166/186/220/260 paper pushing speed 5-20m/min).

Powerful computer operating system with more functions and it can store and memorize things. The storage time can be up to 300,000 hours with self-maintenance of the operating system. Hydraulic components are adopted from Italy, electrical components from France, Germany, Japan, Korea, Taiwan ball lead screw, Linear double guide rails, PLC control system are adopted to monitor all mechanical implementation, its key parts adopt imported bearing of low maintenance.

Technical Parameters:

	Specifications
Model	115F
Cutting width	45" (115 cm)
Max cutting height w/o pressing plate	6.30" (16 cm)
Max. cutting Depth	45" (115 cm)
Max cutting depth w/o assistance pressing plate	0.98" (2.5 cm)
Extended length of working table	28.74" (73 cm)
Height (Working Table)	34.65" - 36.22" (88-92 cm)
Machine Width w/ side working table	104.72" (266 cm)
Total length (Working Table)	88.98" (226 cm)
Cutting speed (r/min)	45

	Specifications
Max. Paper pressure	40000
Power - Main Motor (kw)	4
Motor - Paper Feeding (kw)	0.75
Air Pump (kw)	0.75
Machine Weight (kg)	4000 kg (8818.49 lbs)
Overall Dimension (L x W x H)	100.39" x 63" x 84.65"

Optional Large Side Table Set



Note: The information given above is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. GVDirect™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The above data is purely for reader's consideration, investigation and verification.

GVDIRECT™

Finish Well

GVDirect™ diligently works to ensure our performance lineup of laminate films, digital technologies, equipment, and all things finishing work for our customers to gain consumer attention and market share. GVDirect™ diligently endeavors to deliver value in service, product, and equipment that surpass market demands, support productivity, and uphold social and environmental integrity.

1.877.526.6848

gvdirect.com

GUOWEI F SERIES

130F PROGRAM CONTROL PAPER CUTTER

Japan alternative digital servo control technology; 15-inch colorful touching LCD. The data resolution rate is 0.01mm. It has self-diagnostic function of troubles and displays the operating pattern, and has 300 program units, over 30000 different cutting positions, dynamic display of cutting and running, dynamic tracking, max feeding speed 8-30m/min (166/186/220/260 paper pushing speed 5-20m/min).

Powerful computer operating system with more functions and it can store and memorize things. The storage time can be up to 300,000 hours with self-maintenance of the operating system. Hydraulic components are adopted from Italy, electrical components from France, Germany, Japan, Korea, Taiwan ball lead screw, Linear double guide rails, PLC control system are adopted to monitor all mechanical implementation, its key parts adopt imported bearing of low maintenance.

Technical Parameters:

	Specifications
Model	130F
Cutting width	51" (130 cm)
Max cutting height w/o pressing plate	5.12" (13 cm)
Max. cutting Depth	51" (130 cm)
Max cutting depth w/o assistance pressing plate	0.98" (2.5 cm)
Extended length of working table	28.74" (73 cm)
Height (Working Table)	33.86" - 35.83" (86-91 cm)
Machine Width w/ side working table	104.72" (266 cm)
Total length (Working Table)	94.88" (241 cm)
Cutting speed (r/min)	45

	Specifications
Max. Paper pressure	40000
Power - Main Motor (kw)	4
Motor - Paper Feeding (kw)	0.75
Air Pump (kw)	0.75
Machine Weight (kg)	3900 kg (8598.03 lbs)
Overall Dimension (L x W x H)	102.36" x 60.24" x 76.77"

Optional Large Side Table Set



Note: The information given above is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. GVDirect™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The above data is purely for reader's consideration, investigation and verification.

GVDIRECT™

Finish Well

GVDirect™ diligently works to ensure our performance lineup of laminate films, digital technologies, equipment, and all things finishing work for our customers to gain consumer attention and market share. GVDirect™ diligently endeavors to deliver value in service, product, and equipment that surpass market demands, support productivity, and uphold social and environmental integrity.

1.877.526.6848

gvdirect.com

GUOWEI F SERIES

115F PROGRAM CONTROL PAPER CUTTER

Standard Configuration:

	Brand Model	Origin
Computer Display Screen	WEINVIEW 15 inches color touch screen	Taiwan
Ball-Lead Screw	Ball-Lead Screw	Taiwan
Linear guide	High-precision linear guide	Taiwan
Control center	Panasonic PLC	Japan
Servo drive	Nidec servo drive	Panasonic servo motor
Servo motor	Nidec servo motor	Panasonic servo motor
IR Grating	Import	Italy
Overload protection switch	Schneider	France
Relays	IDEK	Japan
Contactors	Schneider	France
Air switch	LS	Korean
Start button	Moeller	Germany
Locating switch	Schneider	France
Hydraulic Pump	Marzocchi/Brevini	Italy
Hydraulic solenoid valve	Hyde Fuchs	American
Worm Reducer	CEM	Tianjin (American)
Proximity Switch	FOTEK	Taiwan
Bearing	NSK	Japan
Knife	IKS	Shanghai
Safety Relays	LEUZE	Germany

Note: The information given above is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. GVDirect™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The above data is purely for reader's consideration, investigation and verification.