

EXCELAM-PLUS 355DCRSE

14" HOT & COLD LAMINATOR & MOUNTER



Max. Speed
10' per minute



8 minute
Warm Up



110V

GVDIRECT™

Finish Well

GVDirect™ diligently works to ensure our performance lineup of laminate films, digital technologies, equipment, and all things finishing work for our customers to gain consumer attention and market share. GVDirect™ diligently endeavors to deliver value in service, product, and equipment that surpass market demands, support productivity, and uphold social and environmental integrity.

1.877.526.6848

gvdirect.com

EXCELAM-PLUS 355DCRSE

A super multi-task laminator! Laminate up to 14" wide in both 1-sided or 2-sided applications using OPP and PET films. Run a 2-sided edge seal job such as washable menu's and switch over to 1-sided PSA films for floor graphics. Independent temperature control for top and bottom rollers for perfect results every time. Running a big business card job? No problem with the Excelam – load up large rolls using 3" core mandrels and away you go. 110 volt power ensures fast, consistent heating results for long runs. Adjustable tension controls for top and bottom unwinders and powered take-up rewriter helps with special applications such as PSA jobs. Rollers lift up to 3/16" for mounting jobs. Six position adjustable de-curler for 1 sided jobs with perfectly flat finished pieces. Use 1-sided for book covers, business cards etc.

FEATURES:

- This machine has side slitters
- Variable speed (key pad control - up to 10' per minute)
- Variable temperature - key pad control up to 302 degrees Fahrenheit
- Laminates 1.0 mil - 10.0 mil thickness
- Front roller diameter of 2.167"
- Rear roller diameter of 1.181"
- Infrared heated rollers for enhanced adhesion capacity, cooling system.
- Complete with stand and 1" core adaptors and 3" core adaptors.



Key Pad Number Direct & Manual Pressure Adjustment

EXCELAM-PLUS 355 DCRSE Specifications

Max. Laminating Width	355 mm (14")	Max. Mounting Thickness	5 mm (3/16")
Substrate Thickness	80 - 350 g/m ²	Front Roller Diameter	55 mm (2.167")
Max. Laminating Speed	3m (10') per min.	Rear Roller Diameter	30 mm (1.181")
Film Core	1", 3"	Cooling System	Blower
Laminate Films	1.0 mil - 10.0 mil thickness	Type of Main Motor	DC W - Geared Motor 36V70
Operating Temperature	Max. 150°C (302°F)	Type of Rewinder Motor	Link to Main Motor
Warm Up Time	8 Minutes	Stand	X / O
Heating System	Hot Roller Internal Infrared Heater	Dimensions (W x L x H)	23.03" x 17.71" x 17.20"
Speed / Temp. Control	Key Pad Number Direct	Pressure Adjustment	Manual (6step)
Power Requirements	110 Volt		

Note: The information given above is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. GVDirect™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The above data is purely for reader's consideration, investigation and verification.