

SF2 & Face Trimmer

Wire-Stitch Bookletmaker



Up to 2,300 sets
per hour



115 V, 60 Hz



GVDIRECT™

Finish Well

GVDirect™ diligently works to ensure our performance lineup of laminate films, digital technologies, equipment, and all things finishing work for our customers to gain consumer attention and market share. GVDirect™ diligently endeavors to deliver value in service, product, and equipment that surpass market demands, support productivity, and uphold social and environmental integrity.

1.877.526.6848

gvdirect.com

SF2 & Face Trimmer

WIRE-STITCH BOOKLETMAKER

Wire-fed stitching system provides lower operating costs than bookletmakers using pre-formed staples – produces booklets up to 100 pages*. Low maintenance—jogs, stitches, and folds up to 65,000 booklets without replacing wire spools. Runs on-line with a variety of collators (interface is included) including the MBM FC 10 . Easy to use, push-button controls with 6 digit counter. Staple leg adjustment feature allows staple length to be custom fit to the size of book being run. Heavy-duty clutch and bearings. Moveable, magnetic stitching heads. One-step threading for quick and easy set-up. Knife fold with dual fold rollers for crisp, consistent folds. Powered exit conveyor. Transparent safety access covers—machine will not operate with covers in open position. Includes back jog, and stand with casters. Optional activated clinch, and on-line corner/side stitch gate.

OPTIONAL FACE TRIMMER FOR SF 2 BOOKLETMAKER

Operates on-line with SF 2 bookletmaker. Trims booklets up to 100 pages*. Powered exit conveyor – transparent safety access cover—machine will not operate with cover in open position. Features includes jam detection, electrical interface for communication with StitchFold Bookletmaking System, safety interlock, and see through top cover.



FACE TRIMMER



ONE-STEP THREADING

Magnetic stitching heads feature one-step threading for quick and easy set-up.



POWERED CONVEYOR

The powered exit conveyor on the bookletmaker or trimmer stacks booklets neatly.

SF2 Specifications

Sheet Size	Min. 4.75" x 8.5" / Max. 12.75" x 18.5"
Speed	2,300 sets / hour
Sheet capacity	Up to 25 sheets
Dimensions	21" D x 52" W x 24.5" H
Shipping Weight	400 lbs
Electrical	115 V, 60 Hz

Face Trimmer Specifications

Sheet Size	Min. 4.75" x 8.75" / Max. 12.68" x 18.25"
Speed	Up to 2,300 booklets / hour
Capacity	4.00" cut width x 4.13" to fold (trim length) 2 sheets 20# bond thickness Max: 12.71" cut width x 9.00" to fold (trim length) 50 sheets 20# bond thickness (0.20") 0.625" maximum material trim
Booklets	4.25" x 5.5", 5.5" x 8.5", 8.5" x 11", 4.75" x 4.75" "CD"
Output	Indexing conveyor
Dimensions	27.38" H x 26.42" W (Length without discharge table 25.90") Length with fully extended discharge table 48.44"
Footprint	16.50" x 18.38"
Mode	Trim or No-trim
Unit Weight	236 lbs
Electrical	Standard outlet - 115 Volts, 60 Hz, 6 Amps (1/4 HP) Optional: 230 Vac, 50 Hz, 3 Amps

Note: The information given above is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. GVDirect™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The above data is purely for reader's consideration, investigation and verification.