Cyklos Robolam 370




Double Side Laminator / Modular Finishing Units

 Two pairs of silicon heated rollers, easy accessible

 Automatic feeding with overlap or spacing control and double sheet detection



Modular Burst
separator device



Features:

- Any film thickness and type
- Quick set roll holders
- Small footprint
- Foil cooling device

	Specifications
Paper Size	Min. 9.84" x 5.91" Max. 14.37" x 24.41" (39.37")
Speed	26.25'/min (8 m/min)
Roll Size	Max. 9,840' (1.0 Mil)
Paper Grammage	135 - 400 g/m ²
Loading Capacity	0.79"
Roll Core	3" Core

	Specifications
Footprint	66.93" x 27.17" x 49.21"
Weight	Net 292 lbs (132.5 kg) (Incl. RoboBurst, Delivery table)
Voltage / Frequency	220 V / 50Hz / 15 A
Optional Accessories	RoboBurst, RoboCut feeding table extension top and bottom perforating foiling kit

Note: The information given above is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. GVDirect™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The above data is purely for reader's consideration, investigation and verification.



GVDirect™ diligently works to ensure our performance lineup of laminate films, digital technologies, equipment, and all things finishing work for our customers to gain consumer attention and market share. GVDirect™ diligently endeavors to deliver value in service, product, and equipment that surpass market demands, support productivity, and uphold social and environmental integrity.