

COMPACT 5800i

Shrink Packaging Machine



GVDIRECT™

Finish Well

GVDirect™ diligently works to ensure our performance lineup of laminate films, digital technologies, equipment, and all things finishing work for our customers to gain consumer attention and market share. GVDirect™ diligently endeavors to deliver value in service, product, and equipment that surpass market demands, support productivity, and uphold social and environmental integrity.

1.877.526.6848

gvdirect.com

COMPACT 5800i

Commercial quality shrink machine made for the fast lane!

With electronic heat control, magnetic hold down and intelligent sealing system(22"x17.3") your shrink jobs will be handled efficiently and economically.

- Maximum Product Dimensions: 17.7"x11.8"x5.9"
- Packaging Speed: 7-12 packs/min
- Requirements: Tri-phase Electricity, POF Shrink Film



COMPACT 5800i Specifications

Max Film Width	19.7" (500 mm)
Installed Power	230V, 1 phase, 17 Amp
Consumption	5 kW (Max.)/ 3 kW (Average)
Chamber Size	22.84" x 17.33" x 9.85" (580 x 440 x 250 mm)
Dimensions (AxBxCxD)	48.03" x 28.74" x 10.62" (1220 x 730 x 1140 x 270 mm)
Palletized Size (WxLxH)	31.5" x 47.25" x 30.31" (800 x 1200 x 770 mm)
Weight	265 lb (Net) / 330 lb {120 kg (Net) / 150 kg (Gross)}

Note: The information given above is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. GVDirect™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The above data is purely for reader's consideration, investigation and verification.