

Overlamine Thermal Roll Film

Talent™ GeniusMatte™ is a scuff resistant laminating film provides a significantly higher resistance to scuffing and scratching over standard matte films, while providing a soft tactile feel or consumer engagement. **Talent™ GeniusMatte™** laminating film allows for the bonding of spot UV coating, glues, and foil stamping with ease.

KEY BENEFITS

- Velvety Matte Finish
- Extreme Surface Hardness
- Fingerprint and Smudge Resistant
- Scuff and Burnish Resistant
- Reduce Spoilage
- Accepts Spot UV
- Glueable and Stampable



COMMON APPLICATIONS

- Promotional and Presentation Pieces
- High Use Pocket Folders
- Business Cards
- Soft and Hard Cover Books
- Cosmetics Packaging
- Packaging and Folding Cartons
- Rigid Boxes

Properties	Test Method / Standard	Value	Unit
Thickness	DINEN ISO 534	33	µm
Substance/Grammage	ISO 536	23,96	g/m ²
Yield	DIN 53375	33,89	m ² /kg
Tensile Strength at Break MD	ASTM D882	59,1	N/mm ²
Tensile Strength at Break TD	ASTM D882	124,2	N/mm ²
Elongation at Break MD	ASTM D882	187	%
Elongation at Break TD	ASTM D882	98	%
Gloss Angle of Incidence / Observation 60°/60°	ASTM D2457	2-3	GE
Haze	ASTM D1003	88,3	%
Surface Tension	DIN 55660-2	42	mN/m

MD = Main Direction TD = Transverse Direction DIN = Deutsche Industrie Norm (German Industry Norm)
 GE = Gloss Units DIN EN ISO = German, European & International Standard ASTM = American Test Method

Note: The information given above is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. GVDirect™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The above data is purely for reader's consideration, investigation and verification.