



Premium Lamination Film

AVAILABLE IN: 1.2 mil - 10.0 mil - 1" - 3" Core / Various Roll Lengths and Widths

High clarity thermal low melt lamination film. Manufactured with 100% EVA adhesive and a solvent-based primer for long term durability, our premium proprietary adhesive "wets out" at 240°F. Ideal for sell sheets, menus, plastic cards, posters and more. Available in Gloss and Matte finishes from 1.2 mil – 10.0 mil thicknesses.

KEY BENEFITS

- Polyester base offers advanced surface properties
- Offers good dimensional stability during one-side or both side lamination jobs
- Low melt co-polymer ensures high bond strength at lower lamination temperatures
- Excellent Ink Adhesion and Bond Strength*

SUGGESTED USES

- Leaflets
- Posters
- Menu Cards
- Carton Boxes

PHYSICAL CHARACTERISTICS

Properties	Unit	Test Method	Products					
Thickness	Mil		1.2	1.5	1.7	3.0	5.0	10.0
	Micron		30	38	42	75	125	250
Lamination Temperature		MFGR	110° ~ 130°C (230° ~ 260°F)					
Surface Finish			Gloss / Matte					
Composition			Various compositions available - 0.5/2.5, 12/25, 12/32, 1/2, 2/1, 1/4, 2/3, 3/2, 2/8, 4/6, 7/3					



Finish Well

GVDirect™ diligently works to ensure our performance lineup of laminate films, digital technologies, equipment, and all things finishing work for our customers to gain consumer attention and market share. GVDirect™ diligently endeavors to deliver value in service, product, and equipment that surpass market demands, support productivity, and uphold social and environmental integrity.

1.877.526.6848

gvdirect.com